



Fout! Geen onderwerp opgegeven.

Picture model: 108-06
MULTI-PORT VALVE WITH EXTENDED INLET

Standard materials				
Body, Bonnet	AISI 316 (L)			
Needle point	Rotating ceramic ball Al ₂ O ₃			
Stem	AISI 316 Ti with chromium-carbide diffusion coating			
Connections				
Process	1/2-14 NPT (M)	ANSI / ASME B1.20.1		
Instrument	3 x 1/2-14 NPT (F)	ANSI / ASME B1.20.1		
Stem packing	Code	P/T		Material
Teflon (PTFE)	xxx-01	413 barg 38°C 200 barg 230°C 6000 psig 100°F 3000 psig 450°F		AISI 316 (L)
VITON	xxx-06	600 barg 38°C 200 barg 200°C 9000 psig 100°F 3000 psig 400°F		AISI 316 (L)
Grafoil	xxx-05	413 barg 38°C 200 barg 400°C 6000 psig 100°F 3000 psig 750°F		AISI 316 (L)
Other packingmat.	Silicon, Kalrez, Supagraf Premier, EPDM, Elast-o-lion			
Special alloys				
	Alloy 400	Alloy C-276	TITAN	DUPLEX 1.4462
Model	xxx-02	xxx-03	xxx-04	xxx-20
Stem packing	PTFE	PTFE	PTFE	VITON O-ring
	Alloy 825	Alloy 625	Alloy 254Smo (6M0)	
Model	xxx-12 (825)	xxx-12	xxx-11	Other on request
Stem packing	PTFE	PTFE	PTFE	
Optional				Add code
Oxygen cleaned				xxx-xx/C
G-threaded connections				xxx/B -xx
MonelK500 (NACE compliance)				xxx-xx5
10.000 psi solution				xxx/10K-xx
Length of inlet extended to 50 mm				xxx/L-xx
Process side 3/4"NPT M				Xxx/34-xx
Accessories				Add code
Blind plug 1/2"NPT M				50.900
Purge plug 1/2" NPT M				52.900

Model 108

